Rittal – The System.

Faster – better – everywhere.





CP 6320.300

Operating housing with handle strips

State: 2025-12-08 (Source: rittal.com/ca-en)



CP 6320.300 - Operating housing with handle strips

Command panel with handle strips in contemporary design of sheet steel, with \emptyset 130 mm support arm cut-out to fit CP 60/120/180 support arm system, service access optionally from the front or rear, aluminum front panel easily removable for machining, protection category IP 55

Features

Model No.	CP 6320.300
Material	Housing and door: Carbon steel
	Handle strips: Aluminum
	Front panel: Aluminum
	Cover caps: Plastic
Surface finish	Housing and door: Dipcoat primed, powder-coated on the outside, textured paint
	Handle strip: Natural anodized
	Front panel: Natural anodized.
Color	Housing and door: RAL 7035
	Handle strip: Natural anodized
	Front panel: Natural anodized.
	Cover caps: Similar to RAL 7024
	Cover caps. Similar to NAL 7024
Supply includes	Housing with cut-out and reinforcement for support arm connection Ø 130 mm
	Front with maximum cut-out, covered with easily machinable 3 mm
	aluminum front panel
	Side handle strips and cover caps
	Cam lock with 3 mm double-bit insert
	Integral interior mounting bracket with TS system punchings
Dimensions	Width: 380 mm
	Height: 380 mm
	Depth: 210 mm
Protection category IP to IEC 60 529	IP 55
Version	Service access from rear

© Rittal 2025 2

Features

Note	The support arm connection and door catch may be swapped over by rotating the enclosure
	Optional: Support arm connection Ø 130 mm, preformed off-center
	in the reinforcement plate, easily drilled out
	Lock systems for servicing access from the rear: 27 mm lock
	inserts, type A, lock cylinder, plastic handles and T-handles, type B
Base material	Aluminum
Lock	Lock version: Cam
	No. of locks: 1
	Lock Insert: 3 mm double-bit
Packaging unit	1 pc(s).
Net weight	9.041
Gross weight	9.517
EAN	4028177693982
ECLASS 8.0	27180505

Approvals

Explanations	Declaration of conformity
	Declaration of conformity UK

© Rittal 2025 3