

Rittal – The System.

Faster – better – everywhere.



CP 6380.400

Optipanel

State: 2026-01-29 (Source: [ittal.com/ca-en](https://www.ittal.com/ca-en))



ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

CP 6380.400 - Optipanel

Aluminum housing, high thermal conductivity for optimum passive heat dissipation. For smaller panels and control solutions. Extremely slim design, requires slightly more space than the installations themselves.



Features

| | |
|-----------------|---|
| Model No. | CP 6380.400 |
| Version | Support arm connection, rectangular 120 x 65 mm |
| Benefits | Aluminum housing, high thermal conductivity for optimum passive heat dissipation. Low weight coupled with high stability Compatible with all Rittal stand and support arm systems |
| Material | Housing: Extruded aluminum section Corner pieces: Die-cast zinc Corner protectors: Plastic |
| General color | Natural anodized |
| Color | Housing: Natural anodized. Corner pieces: RAL 7035 Corner protectors: Similar to RAL 7024 |
| Supply includes | Housing with hinged rear panel Seals Seals and assembly components for front panels |

Features

| | |
|--------------------------------------|---|
| Dimensions | Width: 564 mm Height: 444 mm Depth: 110 mm |
| Installation depth | 100 mm |
| Protection category IP to IEC 60 529 | IP 65 |
| Suitable for front panel width | 520 mm |
| Suitable for front panel height | 400 mm |
| Version | Service access from rear |
| Note | The support arm connection may be swapped over by rotating the enclosure 3 mm double-bit lock insert may be exchanged for 41 mm lock inserts, plastic handles and T handles, type C Rear panel hinges on the longest enclosure side |
| Base material | Aluminum |
| Lock | Lock version: Cam No. of locks: 2 Lock Insert: 3 mm double-bit |
| Packaging unit | 1 pc(s). |
| Net weight | 7.755 |
| Gross weight | 8.163 |
| Customs tariff number | 94032080 |
| EAN | 4028177663152 |
| ETIM 9 | EC002504 |
| ECLASS 8.0 | 27180505 |

Approvals

| | |
|-----------|--------------------|
| Approvals | UL + C-UL (listed) |
|-----------|--------------------|

Approvals

Explanations

Declaration of conformity
Declaration of conformity UK