Rittal – The System.

Faster – better – everywhere.





IW 6900.300 PC Enclosure Systems

State: 2025-12-19 (Source: rittal.com/ca-en)



IW 6900.300 - PC Enclosure Systems Housing for Tower PC

Housing for commercially available tower PCs.

Features

Model No.	IW 6900.300	
Version	Roof prepared for mounting worktop or for mounting underneath surfaces	
	Roof prepared for mounting cast feet or for mounting on surfaces	
Product description	Standard, commercially available PC towers, up to W/H/D: 250 x 530 x 600 mm (max. 20 kg) can be securely attached to the floor of bolted to the door by means of an enclosed retaining strap. The rea interfaces of the PC are easily accessible with the door open. Because the filter fan unit is already pre-installed, the housing is ready for immediate use.	
Material	Housing: Carbon steel Door: Carbon steel	
	Design strips: Aluminum	
Surface finish	Housing: Powder-coated, textured paint Door: Powder-coated	
Color	Housing: RAL 7035	
	Door: RAL 7015	
	Design strips: RAL 7035	

© Rittal 2025

Features

Supply includes	Housing of all-round solid construction	
	R/h door catch	
	Door with base screw-fastened on the inside	
	Side cam lock	
	Double-bit lock insert	
	Rear panel with two cut-outs for use of the connector gland	
	supplied loose	
	Cable gland M20, brass, nickel-plated Outlet filter fitted in left side panel	
	Door-operated switch, supply socket for 230 V power supply, socket	
	strip with 3 sockets and overvoltage protection	
Dimensions	Width: 760 mm	
	Height: 760 mm	
	Depth: 300 mm	
Protection category IP to IEC 60 529	IP 54 in conjunction with connector gland supplied loose	
Protection category NEMA	NEMA 12 in conjunction with connector gland supplied loose	
Base material	Aluminum	
Packaging unit	1 pc(s).	
Net weight	34.2	
Gross weight	36	
EAN	4028177438712	
ECLASS 8.0	27180501	

Approvals

Declaration of conformity

© Rittal 2025 3