

Rittal – The System.

Faster – better – everywhere.



DK 7010.180 Access control

State: 2025-09-17 (Source: [rittal.com/ca-en](https://www.rittal.com/ca-en))

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



DK 7010.180 - Access control for CMC III, PDU, LCP, IoT interface

Access control

Features

Model No.	DK 7010.180
Version	Access control
Benefits	Fast connection and automatic detection via plug & play Power is supplied via the CAN bus interface.
Applications	Enclosure monitoring in IT, industry and facility management Monitoring enclosures, rooms and containers in the field of IT.
Function principle	For connecting two handles and two reader units to monitor doors Integrated IR access sensor Built-in vandalism sensor
Material	Plastic
Surface finish	Front: Smooth Housing: Textured
Color	RAL 9005
Supply includes	Sensor Mounting panel Assembly components
Connection to the CAN bus	Direct
Interfaces	2 x RJ45 CAN bus 2 x RJ12 2 x flat-pin connectors Socket
Dimensions	Width: 110 mm Height: 30 mm Depth: 40 mm
Operating temperature range	0 °C...55 °C

Features

Ambient humidity (non-condensing)	5...95 %
Packaging unit	1 pc(s).
Customs tariff number	85311095
ETIM 9	EC002627