## Rittal – The System.

Faster – better – everywhere.





# DK 7030.223 Coded lock

State: 2025-11-01 (Source: rittal.com/ca-en)



## DK 7030.223 - Coded lock for CMC III and IoT interface

For access management of doors.

#### **Features**

Model No.	DK 7030.223
Product description	For access management of doors.
Benefits	Individual numerical codes with up to eight digits One reader system may be used for multiple handles, provided they are linked to the same CMC III system or IoT interface High security due to the four-eyes principle
Function principle	Direct connection to CMC III access control or CMC III door control module Optical (LED) and audible (alarm sound) status indicator Management of authorizations via CMC III system, IoT interface, or RiZone Door opening by a maximum of two linked numerical codes (foureyes principle) Control via CMC III from: Online VX comfort handle, automatic door opening system (ventilation flaps), relay outputs of the CMC III
Material	Plastic
Color	RAL 9005
Supply includes	Coded lock Connection cable 2.9 m Adapter for aluminum-glazed door for VX IT Assembly components
Installation options	On VX IT doors  Next to compartment doors
Dimensions	Width: 50 mm Height: 190 mm Depth: 25 mm
Packaging unit	1 pc(s).

© Rittal 2025

## **Features**

Gross weight	0.271
Customs tariff number	83015000
EAN	4028177936539
ETIM 9	EC002627
ECLASS 8.0	27189253

## **Approvals**

Approvals	UL + C-UL (listed)
Explanations	Declaration of conformity

© Rittal 2025 3