## Rittal – The System.

Faster – better – everywhere.





# IT 7030.230 Transponder reader

State: 2025-11-17 (Source: rittal.com/ca-en)



# IT 7030.230 - Transponder reader for CMC III

Readers for controlled door opening by means of transponder.

#### **Features**

Model No.	IT 7030.230
Version	Transponder reader
Product description	CMC III transponder reader for releasing rack or compartment doors, connection to the CMC III Processing Unit via CMC III CAN bus access, clearance by transponder card.
Benefits	Fast connection and automatic detection via plug & play Status display via integral LED
Applications	For mounting on enclosure doors or next to a room door.
Function principle	The door is released after authentication by the user.  Access rights can be set via the software of the CMC III Processing Unit or of the IoT interface  Power is supplied via the connection to the CMC III CNA bus unit access.
Material	Plastic
Color	Housing: RAL 7035 Front: RAL 9005
Supply includes	Transponder reader Connection cable Operating manual Compensating panel for TS 8 glazed door design Assembly components 3 transponder cards
Length of connection cable	3 m
Quantity of participants per IoT interface (max.)	16
Quantity of participants PU compact (max.)	2
Quantity of participants PU (max.)	16

© Rittal 2025

### Features

Note	Max. 5 consumers per PU for power supply via PoE
Transponder tags	ISO 15693 - Mifare 1K
	ISO 15693 - Mifare 4K
	ISO 15693 - I-Code SL2
	ISO15693 - Tag-it
Dimensions	Width: 50 mm
	Height: 190 mm
	Depth: 25 mm
Operating temperature range	0 °C55 °C
Ambient humidity (non-	595 %
condensing)	
Packaging unit	1 pc(s).
Net weight	0.25
Gross weight	0.296
Customs tariff number	85311095
EAN	4028177659582
ETIM 9	EC002627
ECLASS 8.0	27189253

# **Approvals**

Explanations	Manufacturer's declaration
	Declaration of conformity

© Rittal 2025 3