### Rittal – The System.

Faster – better – everywhere.





# DK 7030.233 Transponder reader

State: 2025-12-07 (Source: rittal.com/ca-en)



# DK 7030.233 - Transponder reader for CMC III and IoT interface

For access management of doors.

#### **Features**

Model No.	DK 7030.233
Version	Transponder reader for Mifare, Legic Advant, HID, FeliCa (Legic Prime on request)
Product description	CMC III transponder reader for releasing rack or compartment doors, connection to the CMC III Processing Unit via CMC III CAN bus access, clearance by transponder card.
Benefits	One reader system may be used for multiple handles, provided they are linked to the same CMC III system or IoT interface High security due to the four-eyes principle
Technical specifications	Frequency: 13.56 MHz Frequency RFID
Applications	On VX IT doors Next to compartment doors
Function principle	Direct connection to CMC III access control or CMC III door control module Optical (LED) and audible (alarm sound) status indicator Management of authorizations via CMC III system, IoT interface, or RiZone Door opening by a maximum of two linked numerical codes (foureyes principle) Control via CMC III from: Online VX comfort handle, automatic door opening system (ventilation flaps), relay outputs of the CMC III
Material	Plastic
Color	RAL 9005

© Rittal 2025

#### **Features**

Supply includes	Transponder reader	
	Connection cable 2.9 m	
	Adapter for aluminum-glazed door for VX IT	
	Transponder card Mifare classic	
	Assembly components	
Installation options	On VX IT doors	
	Next to compartment doors	
Transponder tags	ISO14443A - MIFARE Classic	
	ISO14443A - MIFARE Classic EV1	
	ISO14443A - MIFARE DESFire EV1	
	ISO14443A - MIFARE DESFire EV2	
	ISO14443A - MIFARE Plus S, X	
	ISO14443A - MIFARE Smart MX	
	ISO14443A - MIFARE Ultralight	
	ISO14443A - MIFARE Ultralight C	
	ISO14443A - NTAG2xx	
	ISO18092 ECMA-340 - Sony FeliCa	
	ISO15693 - HID iCLASS SE/SR	
	ISO15693 - ICODE SLI	
	ISO15693 - LEGIC Advant	
	ISO15693 - Tag-it	
Dimensions	Width: 50 mm	
	Height: 190 mm	
	Depth: 25 mm	
Packaging unit	1 pc(s).	
Net weight	0.276	
Gross weight	0.28	
Customs tariff number	85311095	
EAN	4028177936546	
ETIM 9	EC002627	
ECLASS 8.0	27189253	

© Rittal 2025 3

## Approvals

Approvals	UL + C-UL (listed)
Explanations	Declaration of conformity

© Rittal 2025