


# Rittal – The System.

Faster – better – everywhere.



## DK 7246.100 Adapter set, 3 U

State: 2026-05-21 (Source: [rittal.com/ca-en](http://rittal.com/ca-en))

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# DK 7246.100 - Adapter set, 3 U for enclosure width 800 mm

To mount individual 482.6 mm (19") components, or as an additional mounting facility at the rear of the enclosure.



## Features

Model No.	DK 7246.100
Version	Installation position, center
Product description	To mount individual 482.6 mm (19") components, or as an additional mounting facility at the rear of the enclosure. The mounting level in the adaptor bracket can be adjusted in the depth in 25 mm increments up to 100 mm, providing sufficient space for cable management if patch panels or splicing boxes are used. Mounting is on the inner mounting level of the frame profile or on an appropriate chassis in the enclosure depth.
Material	Carbon steel
Color	RAL 7035
Height units	3 U
Installation dimensions	Installation depth for components: 482.6 mm Installation width for components: 19"
Packaging unit	2 pc(s).
Net weight	1.14 kg
Gross weight	1.304 kg
PCF/VE (cradle-to-gate)	5 kg CO2 eq (Cat B)

# Features

---

Information regarding the PCF class	Category B: PCF value (cradle-to-gate) calculated approximately on the basis of the product weight and self-declared
Customs tariff number	83024900
ETIM 9	EC002625
ECLASS 8.0	27189234
Product description	DK Adaptor kit, 3 U, For W: 800 mm

---