

Rittal – The System.

Faster – better – everywhere.



DK 7246.100 Adapter set, 3 U

State: 2025-12-07 (Source: [rittal.com/ca-en](https://www.rittal.com/ca-en))

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



DK 7246.100 - Adapter set, 3 U for enclosure width 800 mm

To mount individual 482.6 mm (19") components, or as an additional mounting facility at the rear of the enclosure.



Features

| | |
|-------------------------|---|
| Model No. | DK 7246.100 |
| Version | Installation position, center |
| Product description | To mount individual 482.6 mm (19") components, or as an additional mounting facility at the rear of the enclosure. The mounting level in the adaptor bracket can be adjusted in the depth in 25 mm increments up to 100 mm, providing sufficient space for cable management if patch panels or splicing boxes are used. Mounting is on the inner mounting level of the frame profile or on an appropriate chassis in the enclosure depth. |
| Material | Carbon steel |
| Color | RAL 7035 |
| Height units | 3 U |
| Installation dimensions | Installation depth for components: 482.6 mm Installation width for components: 19" |
| Packaging unit | 2 pc(s). |
| Net weight | 1.14 |
| Gross weight | 1.304 |
| PCF/VE (cradle-to-gate) | 5 kg CO2 eq (Cat B) |

Features

| | |
|-------------------------------------|--|
| Information regarding the PCF class | Category B: PCF value (cradle-to-gate) calculated approximately on the basis of the product weight and self-declared |
| Customs tariff number | 83024900 |
| EAN | 4028177186798 |
| ETIM 9 | EC002625 |
| ECLASS 8.0 | 27189234 |