

Rittal – The System.

Faster – better – everywhere.



DK 7246.400 Adapter, 3 U

State: 2025-05-19 (Source: [rittal.com/ca-en](https://www.rittal.com/ca-en))

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



DK 7246.400 - Adapter, 3 U Depth offset 100 mm

Used to recess the 482.6 mm (19") mounting of equipment inside enclosures with a 19" installation in the foremost position, such as server or electronic enclosures.



Features

Model No.	DK 7246.400
Product description	The adapter provides recessed mounting of equipment within the 19" rail. This ensures there is enough space in front of the equipment to integrate patch panels or switches, while utilizing the enclosure depth to the maximum.
Material	Carbon steel
Surface finish	Zinc-plated
Supply includes	Assembly components
Height units	3 U
Installation dimensions	Installation depth for components: 482.6 mm Installation width for components: 19"
Packaging unit	2 pc(s).
Net weight	0.34
Gross weight	0.37
PCF per pack (cradle-to-gate)	1.4 kg CO2 eq (Cat B)
Note on PCF category	Category B: PCF value (cradle-to-gate) based on the product weight, approximately calculated and self-declared
Customs tariff number	73269098

Features

EAN	4028177389830
ETIM 9	EC002625
ECLASS 8.0	27189234