

Rittal – The System.

Faster – better – everywhere.



DK 7752.950 ESD connection point

State: 2026-02-09 (Source: [rittal.com/ca-en](https://www.rittal.com/ca-en))

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



DK 7752.950 - ESD connection point

To protect sensitive electronic components, this standardized connection point (push-button) provides equipotential bonding.



Features

Model No.	DK 7752.950
Product description	There is high risk of grounding issues when carrying out maintenance or conversion work on the enclosure. To protect sensitive electronic components, grounding can be provided through a standardized connection point (push-button). The connection point is connected to the enclosure frame by two screws and is directly conductive.
Material	Carbon steel
Surface finish	Zinc-plated
Supply includes	Assembly components
Packaging unit	1 pc(s).
Net weight	0.032
Gross weight	0.035
PCF/VE (cradle-to-gate)	0.1 kg CO2 eq (Cat B)
Information regarding the PCF class	Category B: PCF value (cradle-to-gate) calculated approximately on the basis of the product weight and self-declared
Customs tariff number	73269098
EAN	4028177325227
ETIM 9	EC002623

Features

ECLASS 8.0

27189234