Rittal – The System.

Faster – better – everywhere.





TS 8226.500 Baying systems TS 8

State: 2025-07-28 (Source: rittal.com/ca-en)



TS 8226.500 - Baying systems TS 8

Due to its symmetrical profile in terms of width and depth, the TS 8 baying system, made from carbon steel, saves considerable space and facilitates easy internal installation. It also allows a baying arrangement on all sides. In addition, the integrated, automatic potential equalization of all enclosure panels and the triple machining of the surface ensures maximum safety.



Features

TS 8226.500
Enclosure frame: Carbon steel, 1.5 mm
Roof: Carbon steel, 1.5 mm
Door: Carbon steel, 2.0 mm
Rear wall: carbon steel, 1.5 mm
Base plates: Carbon steel, 1.5 mm
Mounting panel: Carbon steel, 3.0 mm
Enclosure frame: Dipcoat-primed
Door, roof and rear panel: Dipcoat-primed, powder-coated on the
outside, textured paint
Mounting plate and base plates: Zinc-plated
RAL 7035

© Rittal 2025 2

Features

Supply includes	Enclosure frame Door(s) Right-hand door catch on single-door enclosures may be swapped to the left Roof plate Rear panel 4 eyebolts Lock: 3 mm double-bit
	Base Plates Mounting panel
	Mounting panel 2 TS punched rails, 18 x 38 mm
	2 support strips fitted in the enclosure depth
Dimensions	Width: 1,200 mm
	Height: 2,200 mm
	Depth: 600 mm
Dimensions of mounting plate (W x H)	1,099 mm x 2,096 mm
Protection category IP to EN 60 529	IP 55
Protection category NEMA	NEMA 1 NEMA 12
Type rating according to UL 50E	Type 1 Type 12
IK code	IK09
Number of doors	2
2 supportstrips in depth	Yes
Base material	Carbon steel
Packaging unit	1 pc(s).
Net weight	197.6
Gross weight	208
Customs tariff number	94032080
EAN	4028177250901
ETIM 9	EC000261

© Rittal 2025 3

Features

Approvals

Approvals	Bureau Veritas Lloyds Register of Shipping UL + C-UL (listed)
Certificates	Surface finish
Explanations	Manufacturer's declaration Declaration of conformity Declaration of conformity UK

© Rittal 2025