## Rittal - The System.

Faster – better – everywhere.





VX 8620.051

Base/plinth corner pieces with base/plinth trim panels, front and rear, 100 mm stainless steel

State: 2025-07-25 (Source: rittal.com/ca-en)

NCLOSURES

OWER DISTRIBUTION

CLIMATE CONTROL

T INFRASTRUCTURI

**SOFTWARE & SERVICES** 

# VX 8620.051 - Base/plinth corner pieces with base/plinth trim panels, front and rear, 100 mm stainless steel for VX, TS, VX SE

Base/plinth corner pieces with molded self-positioning to the bayed enclosure system, for use with or without trim panels depending on the application. Large openings in the base/plinth corner piece for best access to the screw-fastening point can be covered using bay and corner covers.

#### **Features**

Model No.	VX 8620.051
Product description	Base/plinth corner pieces with molded self-positioning to the bayed enclosure system, for use with or without trim panels depending on the application. Large openings in the base/plinth corner piece for best access to the screw-fastening point can be covered using bay and corner covers.
Material	Base/plinth corner piece: Stainless steel 1.4301 (AISI 304) Base/plinth trim panels, front/rear: Stainless steel 1.4301 (AISI 304) Corner and baying covers: Plastic
Surface finish	Trim Panel: Brushed, grain 400
Supply includes	4 x base/plinth corner pieces 4 x corner covers 1 x baying cover 2 x base/plinth trim panels, front/rear, 100 mm high Assembly components
Note	Base/plinth trim panels, on the side for closing off a base/plinth unit, for additional stabilization of the bases/plinths to one another, or for interior installation of the bases/plinths  The components of the first generation base/plinth system cannot be combined with the components of the second generation base/plinth system
Dimensions	Height: 100 mm
Suitable for	Width: = 800 mm

© Rittal 2025

2

### **Features**

Type rating according to UL 50E	Type 1
	Type 3R
	Type 4
	Type 4X
	Type 12
Weight/packaging unit	6.5 kg
Packaging unit	2 pc(s).
Net weight	4.78
Gross weight	4.86
Customs tariff number	94039910
EAN	4028177922303
ETIM 9	EC000721
ECLASS 8.0	27182003

# Approvals

Approvals UL + C-UL - FTTA