

# Rittal – The System.

Faster – better – everywhere.



## TS 8800.130 Support Strip

State: 2026-05-23 (Source: [rittal.com/ca-en](http://rittal.com/ca-en))

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# TS 8800.130 - Support Strip for VX, TS, VX SE, TP, AX

For simple attachment of cable ducts, cable conduit holders, contact hazard protection cover plates, equipment installed on the door, cable clamping and attachment.



## Features

Model No.	TS 8800.130
Product description	For simple attachment of cable ducts, cable conduit holders, contact hazard protection cover plates, equipment installed on the door, cable clamping and attachment.
Technical specifications	4.5 mm diameter hole on a 25 mm hole pattern
Material	Carbon steel
Surface finish	Zinc-plated
Supply includes	Assembly components
Length	590 mm
Installation options VX SE	In enclosure width/depth 600 mm, on the inner mounting level
Installation options AX	In enclosure height 700 mm and in enclosure width 600 mm, in conjunction with rail for interior installation AX
Installation options AX stainless steel	In enclosure width + 600 mm
Installation options PC	In enclosure width 600 mm, on the inner mounting level
Installation options IW	In enclosure width/depth 600 mm, on the inner mounting level
Installation options TS	In enclosure width/depth 600 mm, on the inner mounting level

# Features

Installation options TP	In TP pedestal and one-piece console pedestal width 600 mm, in conjunction with rail for interior installation TP, compact enclosure HD
Suitable for	Enclosure type: TS VX SE TP PC IW AX Width/depth: 600 mm
Packaging unit	20 pc(s).
Net weight	5.86 kg
Gross weight	6.165 kg
PCF/VE (cradle-to-gate)	27.96 kg CO2 eq (Cat B)
Information regarding the PCF class	Category B: PCF value (cradle-to-gate) calculated approximately on the basis of the product weight and self-declared
Customs tariff number	73269098
ETIM 9	EC002620
ECLASS 8.0	27189261
Product description	TS support strip, for TS, VX SE, TP, for inner mounting level: for W/D: 600 mm, L: 590 mm

# Approvals

Explanations	PCF-declaration
--------------	-----------------