

Rittal – The System.

Faster – better – everywhere.



TS 8800.340

Captive nut

State: 2026-05-22 (Source: [rittal.com/ca-en](https://www.rittal.com/ca-en))

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



TS 8800.340 - Captive nut

Used on enclosures and rails with rectangular 12.5 x 10.5 mm system punchings. The nuts are inserted from the same side as screw-fastening takes place.



Features

Model No.	TS 8800.340
Product description	The nuts are inserted from the same side as screw-fastening takes place. This allows fastening points at the same height and width across corners. The spring retainer also provides for electrical connection in the system punchings.
Installation options	On the vertical TS, VX SE enclosure section via adapter rail for VX compatibility On the horizontal TS enclosure section On the horizontal VX SE enclosure section, bottom On the horizontal VX SE enclosure section top, in depth On punched rails 23 x 23 mm On mounting chassis 23 x 73 mm On mounting chassis 45 x 88 mm On 23 x 73 mm system chassis On enclosures and rails with rectangular hole profile 12.5 x 10.5 mm
Dimensions	Thread: M6
Thread	M6
Packaging unit	50 pc(s).
Net weight	0.1 kg
Gross weight	0.166 kg
Customs tariff number	73181692

Features

ETIM 9	EC002358
ECLASS 8.0	23110815
Product description	TS Captive nut, for thread M6, for insertion from the front
