Rittal – The System.

Faster – better – everywhere.





TS 8881.500 Baying systems TS 8

State: 2024-04-30 (Source: rittal.com/ca-en)



TS 8881.500 - Baying systems TS 8

Due to its symmetrical profile in terms of width and depth, the TS 8 baying system, made from sheet steel, saves considerable space and facilitates easy internal installation. It also allows a baying arrangement on all sides. In addition, the integrated, automatic potential equalization of all enclosure panels and the triple machining of the surface ensures maximum safety.



Features

Model No.	TS 8881.500
Material	Enclosure frame: Carbon steel, 1.5 mm
	Roof: Carbon steel, 1.5 mm
	Door: Carbon steel, 2.0 mm
	Rear wall: carbon steel, 1.5 mm
	Base plates: Carbon steel, 1.5 mm
	Mounting plate: Carbon steel, 3.0 mm
Surface finish	Enclosure frame: Dipcoat-primed
	Door, roof and rear panel: Dipcoat-primed, powder-coated on the
	outside, textured paint
	Mounting plate and base plates: Zinc-plated
Color	RAL 7035

© Rittal 2024 2

Features

Supply includes	Enclosure frame
	Door(s)
	Right-hand door catch on single-door enclosures may be swapped to the left
	Roof plate Rear panel
	4 eyebolts
	Lock: 3 mm double-bit
	Base Plates
	Mounting plate
	2 TS punched rails, 18 x 38 mm
	2 support strips fitted in the enclosure depth
Dimensions	Width: 800 mm
	Height: 1,800 mm
	Depth: 600 mm
Dimensions of mounting plate (W x H)	699 mm x 1,696 mm
Protection category IP to EN 60 529	IP 55
Protection category NEMA	NEMA 1, 12
Type rating according to UL 50E	Type 1, 12
IK code	IK09
Number of doors	2
2 supportstrips in depth	Yes
Base material	Carbon steel
Packaging unit	1 pc(s).
Weight/packaging unit	125.8 kg
Customs tariff number	94032080
EAN	4028177251083
ETIM 7.0	EC000261
ECLASS 8.0	27180101

© Rittal 2024 3

Approvals

Approvals	Bureau Veritas
	DNV-GL
	Lloyds Register of Shipping
	UL + C-UL (listed)
Certificates	Surface finish
Explanations	Manufacturer's declaration
	Declaration of conformity
	Declaration of conformity UK

© Rittal 2024 4