


**Rittal – The System.**

Faster – better – everywhere.



**SV 9344.330**

**NH Fuse-Switch Disconnectors**

State: 2026-01-20 (Source: [rittal.com/ca-en](https://rittal.com/ca-en))



ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

# SV 9344.330 - NH Fuse-Switch Disconnectors With electronic fuse monitoring

## Features

Model No.	SV 9344.330
Version	For mounting panel assembly. With electronic fuse monitoring
Material	Polyamide Fire behavior corresponding to UL 94 Contact tracks: Electrolytic copper, silver-plated
Color	Chassis: RAL 7035 Cover: RAL 7035/7001
Clamping area for laminated copper bars: for mounting plate assembly	Clamping area width: 50 mm Clamping area height: 10 mm
Cable outlet	Top/bottom
Type of connection (electrical)	Screw M10
Rated operating current max.	630 A
Rated operating voltage	400 V - 690 V, 3~
For NH size	3
Test specification	IEC 60 947-3 IEC 60 269-2 (fuse inserts)
Dimensions	Width: 250 mm Height: 298 mm
Connection of round conductors	10 - 300 mm <sup>2</sup>
Number of poles	3-pole
With electronic fuse monitoring	Yes
Round conductor cross-section	10 - 300 mm <sup>2</sup>

## Features

---

Packaging unit	1 pc(s).
Net weight	4.4
Gross weight	4.444
Copper weight (kg per piece)	1.06
Customs tariff number	85369095
EAN	4028177542051
ETIM 9	EC000249
ECLASS 8.0	27371401

---

## Approvals

---

Approvals	CQC-CCC
Explanations	Declaration of conformity Declaration of conformity UK

---