

Rittal – The System.

Faster – better – everywhere.



RX 9360.535

RiLineX CB device adapter

State: 2026-07-08 (Source: [rittal.com/ca-en](https://www.rittal.com/ca-en))

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



RX 9360.535 - RiLineX CB device adapter

RiLineX CB device adapter (3-pole, max. 630 A) for 60 mm busbar systems. The device width is 145 mm. Thanks to the Easy-Fix concept, adapter and switch installation can be carried out independently of each other. This concept is available for all popular manufacturers. The adapter has tool-free snap-on mounting with semi-automatic adjustment of the rail thickness between 5 and 10 mm. The cable outlet can be adapted to individual requirements by simply converting the outlet at the bottom or top.



Features

| | |
|-------------------------------------|--|
| Model No. | RX 9360.535 |
| Version | Easy Fix |
| Benefits | Direct mounting of compact circuit breaker MCCB on the board Snap-on mounting up to 250 A and simple adjustment to busbar thickness 5/10 mm Quick and easy pre-assembly of standard switch types outside the control cabinet |
| Material | Polyamide (PA 6) Fire behavior corresponding to UL 94 |
| Color | RAL 9005 RAL 35745 |
| Supply includes | Incl. 3 clamp covers |
| Protection category IP to IEC 60529 | IP 2XB |

Features

| | |
|---|--|
| Rated impulse withstand voltage U _{Imp} | 8 kV |
| Rated voltage | 690 V AC 600 V AC (UL) |
| Rated insulation voltage U _i | 1,000 V |
| Contamination level | 3 |
| Number of poles | 3-pole |
| Cable outlet | Top/bottom |
| Type of connection (electrical) | Screw M10 |
| Cross-section | 29 mm ² 6 mm ² |
| To fit manufacturer (model) | Easily find the right device adapter with our selection guide in the Downloads area. |
| Suitable for busbar system | RiLineX RiLine60 |
| Fundamental frequency | 50...60 Hz |
| Ambient humidity (non-condensing) | 10...90 % |
| Suitable for busbars | 15 x 5/10 20 x 5/10 30 x 5/10 |
| Operating temperature range | -25 °C...55 °C |
| Storage temperature range | -25 °C...75 °C |
| Dimensions | Width: 145 mm Height: 325.8 mm Depth: 76.4 mm |
| Fire load | 22.239 MJ/m ² |
| Packaging unit | 1 pc(s). |
| Net weight | 5 kg |
| Gross weight | 5.206 kg |

Features

| | |
|------------------------------|--|
| Copper weight (kg per piece) | 2.64 |
| PCF/VE (cradle-to-gate) | 30.05 |
| Customs tariff number | 85369095 |
| ETIM 9 | EC001531 |
| Product description | RX CB device adapter 630 A, 3-pole, version: Easy Fix, W: 140 mm |

Approvals

| | |
|--------------|--|
| Approvals | UL + C-UL (listed) |
| Explanations | Declaration of conformity PCF-declaration |
