Rittal - The System.

Faster – better – everywhere.





RX 9360.603 RiLineX CB device adapter

State: 2025-12-08 (Source: rittal.com/ca-en)



RX 9360.603 - RiLineX CB device adapter

RiLineX CB device adapter (3-pole, max. 160 A) for 60 mm busbar systems. The device width is 81 mm. The "universal" version with sliding nuts offers maximum flexibility for switch installation. The adapter has tool-free snap-on mounting with semi-automatic adjustment of the rail thickness between 5 and 10 mm. Version for cable outlet at the top.



Features

Model No.	RX 9360.603
Version	universal
Benefits	Direct mounting of compact circuit breaker MCCB on the board Snap-on mounting up to 250 A and simple adjustment to busbar thickness 5/10 mm Quick and easy pre-assembly of standard switch types outside the control cabinet
Material	Polyamide (PA 6) Fire behavior corresponding to UL 94
Color	RAL 9005 RAL 35745
Protection category IP to IEC 60 529	IP 2XB
Rated impulse withstand voltage Ulmp	12 kV
Rated voltage	690 V AC 690 V DC 600 V AC (UL)
Rated insulation voltage	1,000 V
Overvoltage category	4

© Rittal 2025 2

Features

Contamination level	3
Clamping area for laminated copper bars (W x H)	9 x 6 mm
Number of poles	3-pole
Cable outlet	Тор
Type of connection (electrical)	Box terminal
To fit manufacturer (model)	Our selection aid, available in the Downloads section, helps you to easily find a matching component adaptor.
Suitable for busbar system	RiLineX RiLine60
Fundamental frequency	5060 Hz
Ambient humidity (non-condensing)	1090 %
Suitable for busbars	15 x 5/10 20 x 5/10
	30 x 5/10
Operating temperature range	-25 °C55 °C
Storage temperature range	-25 °C75 °C
Dimensions	Width: 81.9 mm
	Height: 251.4 mm
	Depth: 50.8 mm
Packaging unit	1 pc(s).
Net weight	1.21
Gross weight	1.217
Customs tariff number	39269097

Approvals

Approvals

Explanations

Declaration of conformity

© Rittal 2025