Rittal - The System.

Faster – better – everywhere.





RX 9360.625 RiLineX CB device adapter

State: 2025-11-28 (Source: rittal.com/ca-en)



RX 9360.625 - RiLineX CB device adapter

RiLineX CB device adapter (3-pole, max. 400 A) for 60 mm busbar systems. The device width is 145 mm. The "universal" version with sliding nuts offers maximum flexibility for switch installation. The adapter has tool-free snap-on mounting with semi-automatic adjustment of the rail thickness between 5 and 10 mm. The cable outlet can be adapted to individual requirements by simply converting the outlet at the bottom or top.



Features

Model No.	RX 9360.625	
Version	universal	
Benefits	Direct mounting of compact circuit breaker MCCB on the board Snap-on mounting up to 250 A and simple adjustment to busbar thickness 5/10 mm Quick and easy pre-assembly of standard switch types outside the control cabinet	
Material	Polyamide (PA 6) Fire behavior corresponding to UL 94	
Color	RAL 9005 RAL 35745	
Supply includes	Incl. 3 connection compartment covers, 2 crossbars and fastening material	
Protection category IP to IEC 60 529	IP 2XB	
Rated impulse withstand voltage UImp	12 kV	

© Rittal 2025 2

Features

Rated voltage	690 V AC 690 V DC 600 V AC (UL)
Rated insulation voltage	1,000 V
Overvoltage category	4
Contamination level	3
Number of poles	3-pole
Cable outlet	Top/bottom
Type of connection (electrical)	Screw M10
To fit manufacturer (model)	Our selection aid, available in the Downloads section, helps you to easily find a matching component adaptor.
Suitable for busbar system	RiLineX RiLine60
Fundamental frequency	5060 Hz
Ambient humidity (non-condensing)	1090 %
Suitable for busbars	15 x 5/10 20 x 5/10 30 x 5/10
Operating temperature range	-25 °C55 °C
Storage temperature range	-25 °C75 °C
Dimensions	Width: 145 mm Height: 325.8 mm Depth: 76.4 mm
Packaging unit	1 pc(s).
Net weight	3.6
Gross weight	3.8
Copper weight (kg per piece)	1.652
Customs tariff number	85369095
EAN	4028177997073

© Rittal 2025 3

Features

ETIM 9	EC001531

Approvals

Approvals	UL + C-UL (listed)
Explanations	Declaration of conformity

© Rittal 2025