


Rittal – The System.

Faster – better – everywhere.



RX 9360.730

RiLineX device adapter

State: 2026-01-25 (Source: [ittal.com/ca-en](https://www.ittal.com/ca-en))

RX 9360.730 - RiLineX device adapter

Component adapter 45 mm. Snap-on mounting of components.



Features

Model No.	RX 9360.730
Version	With connection cable
Benefits	<p>For mounting equipment for top-hat rail mounting, e.g. motor starter</p> <p>Pre-assembled connection cable AWG 14 - 2 (16 A - 100 A)</p> <p>Simple connector lock for component support rails</p> <p>Optional component anti-slip guard</p> <p>Snap-on mounting and easy adjustment on busbar thickness 5/10 mm</p> <p>Easy mounting</p> <p>Reduction of article variety through coordinated accessories</p>
Material	<p>Polyamide (PA 6)</p> <p>Fire behavior corresponding to UL 94</p>
Color	<p>RAL 9005</p> <p>RAL 35745</p>
Connection cables (AWG)	AWG 10
Rated current of round conductor	40 A
Rated current of round conductor (UL)	40 A
Cable outlet	Top
For bar systems with center-to-center spacing	60 mm
Length of connection cable	160 mm

Features

Number of poles	3-pole
Suitable for busbar system	RiLineX RiLine60
Dimensions	Width: 45 mm Height: 239.4 mm Depth: 36.2 mm
Support rails Qty/height	1 / 10 mm
Suitable for busbars	15 x 5/10 20 x 5/10 30 x 5/10
Rated voltage	690 V AC 600 V AC (UL) 600 V DC (UL)
Overvoltage category	4
Contamination level	3
Standards	IEC 61 439-1/-2 UL 508
Protection category IP to IEC 60 529	IP 2XB
Operation humidity max	90 %
Operating temperature range	-5 °C...55 °C
Storage temperature range	-25 °C...75 °C
Ambient humidity (non-condensing)	10...90 %
Packaging unit	4 pc(s).
Net weight	1.42
Gross weight	1.45
Copper weight (kg per piece)	0.088
Customs tariff number	85369095
EAN	4028177997011

Features

ETIM 9

EC001531

Approvals

Approvals	UL + C-UL (listed)
Explanations	Declaration of conformity