Rittal – The System.

Faster – better – everywhere.





RX 9360.780 RiLineX device adapter

State: 2025-11-28 (Source: rittal.com/ca-en)



RX 9360.780 - RiLineX device adapter

Component adapter 54 mm. Snap-on mounting of components.

Features

| RX 9360.780 |
|---|
| KA 9300.760 |
| With connection cable |
| For mounting equipment for top-hat rail mounting, e.g. motor starter Pre-assembled connection cable AWG 14 - 2 (16 A - 100 A) Simple connector lock for component support rails Optional component anti-slip guard Snap-on mounting and easy adjustment on busbar thickness 5/10 mm Easy mounting Reduction of article variety through coordinated accessories |
| Polyamide (PA 6) Fire behavior corresponding to UL 94 |
| RAL 9005 RAL 35745 |
| AWG 4 |
| 80 A |
| 80 A |
| Тор |
| 60 mm |
| 130 mm |
| 3-pole |
| RiLineX RiLine60 |
| |

© Rittal 2025

Features

| Dimensions | Width: 54 mm Height: 239.4 mm Depth: 36.2 mm |
|---|--|
| Support rails Qty/height | 1 / 10 mm |
| Suitable for busbars | 15 x 5/10 20 x 5/10 30 x 5/10 |
| Rated voltage | 690 V AC 600 V AC (UL) 600 V DC (UL) |
| Overvoltage category | 4 |
| Contamination level | 3 |
| Standards | IEC 61 439-1/-2 UL 508 |
| Protection category IP to IEC 60 529 | IP 2XB |
| Operation humidity max | 90 % |
| Operating temperature range | -5 °C55 °C |
| Storage temperature range | -25 °C75 °C |
| Ambient humidity (non- condensing) | 1090 % |
| Packaging unit | 4 pc(s). |
| Net weight | 2.12 |
| Gross weight | 2.15 |
| Copper weight (kg per piece) | 0.209 |
| Customs tariff number | 85369095 |
| EAN | 4028177996984 |
| ETIM 9 | EC001531 |

© Rittal 2025 3

Approvals

| Approvals | UL + C-UL (listed) |
|--------------|---------------------------|
| Explanations | Declaration of conformity |

© Rittal 2025