

Rittal – The System.

Faster – better – everywhere.



RX 9361.300

RiLineX connection adapter

State: 2026-05-21 (Source: [rittal.com/ca-en](https://www.rittal.com/ca-en))

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



RX 9361.300 - RiLineX connection adapter

Connection adapter RiLineX busbar platform. Suitable for double connection (bar). Freely selectable phase distance. Only suitable for 10 mm busbars.



Features

| | |
|---|---|
| Model No. | RX 9361.300 |
| Benefits | Mounting on the busbar system and cable connection with just one screw |
| Material | Polyamide (PA 6) Fire behavior corresponding to UL 94 |
| Color | RAL 9005 |
| Rated current (max.) | 1,500 A |
| Rated current max. | 1,500 A |
| Rated current laminated copper busbar | 1,500 A |
| Rated current laminated copper busbar (UL) | 1,380 A |
| Electrical UL ratings (SCCR) | 52.5 kA - 600 V, RMS, unprotected 100 kA - 480 V, circuit breaker max. 800 A, DIVQ/7 100 kA - 600 V, fuse class L max. 2000 A, JDDZ/7 |
| Cable outlet | Top/bottom |
| For bar systems with center-to-center spacing | 60 mm |

Features

| | |
|--|--|
| Number of poles | 1-pole |
| Suitable for busbar system | RiLineX RiLine60 |
| Dimensions | Width: 72.3 mm Height: 119.4 mm Depth: 117.4 mm |
| Clamping area for laminated copper bars (W x H) | 50 x 20 mm |
| Suitable for busbars | 15 x 10 20 x 10 30 x 10 |
| Rated voltage | 1,000 V AC 1,500 V DC 600 V AC (UL) 600 V DC (UL) |
| Overvoltage category | 4 |
| Contamination level | 3 |
| Standards | IEC/EN 61439-1 UL 508 |
| Rated impulse withstand voltage U _{Imp} | 12 kV |
| Rated insulation voltage U _i | 1,000 V |
| Protection category IP to IEC 60529 | IP 2XB |
| Maximum operating air humidity | 90 % |
| Operating temperature range | -5 °C...55 °C |
| Storage temperature range | -25 °C...75 °C |
| Ambient humidity (non-condensing) | 10...90 % |
| Number of connections | 2 |
| Packaging unit | 1 pc(s). |

Features

| | |
|-------------------------|---|
| Net weight | 0.65 kg |
| Gross weight | 0.688 kg |
| PCF/VE (cradle-to-gate) | 2.69 |
| Customs tariff number | 85369010 |
| ETIM 9 | EC001531 |
| Product description | RX connection adapter 1-pole, WH: 72x120 mm, clamping area WH: 50x10 mm |

Approvals

| | |
|--------------|--|
| Approvals | UL + C-UL (listed) |
| Explanations | Declaration of conformity PCF-declaration |