Rittal - The System.

Faster – better – everywhere.





RX 9362.030 RiLineX NH fuse switch disconnector

State: 2025-11-15 (Source: rittal.com/ca-en)



RX 9362.030 - RiLineX NH fuse switch disconnector

RiLineX NH fuse-switch-disconnector in size 00 for 60 mm busbar systems. The cover is lockable, sealable and features visual fuse monitoring. The safe voltage test takes place via the integrated measurement points on the cover. The NH fuse-switch-disconnectors have a park position to simplify maintenance work. Connection design with box terminal for connecting round conductors min. 1.5 bis max. 95 mm². Cable outlet can be individually converted at the top or bottom.



Features

Model No.	RX 9362.030
Benefits	Cover, lockable and sealable
	Voltage test through separate opening
	Snap-on mounting up to 250 A and simple adjustment to busbar
	thickness 5/10 mm
	Tool-free conversion of the cable outlet
	Park position for simplified maintenance work
	All variants also with electronic fuse monitoring
Material	Polyamide (PA 6)
	Fire behavior corresponding to UL 94
	Contact tracks: Electrolytic copper, silver-plated
Color	RAL 9005
	RAL 35745
For bar systems with center-to- center spacing	60 mm
Cable outlet	Top/bottom
Type of connection (electrical)	Box terminal
Rated insulation voltage	1,000 V

© Rittal 2025 2

Features

Rated operating current max.	160 A
Rated operating voltage	690 V AC
For NH size	00
Test specification	IEC 60 947-3 IEC 60 269-2 (fuse inserts)
Dimensions	Width: 106 mm Height: 195 mm Depth: 105 mm
Operating temperature range	-5 °C35 °C
Storage temperature range	-25 °C70 °C
Suitable for busbars	15 x 5/10 20 x 5/10 30 x 5/10
Suitable for busbar system	RiLineX RiLine60
Number of poles	3-pole
Utilization category	AC-23B (400 V/100 A) AC-22B (500 V/100 A) DC-22B (250 V/100 A)
Contamination level	3
Protection category IP to IEC 60 529	IP 2XB
Fire load	14.2 MJ/m²
Connection of round conductors, fine wire without wire end ferrule	1.5 - 95 mm²
Connection of round conductors, fine wire with wire end ferrule	1.5 - 95 mm²
Power dissipation (max.)	22 W
Packaging unit	1 pc(s).
Net weight	0.946
Gross weight	1.039

© Rittal 2025 3

Features

Copper weight (kg per piece)	0.409
Customs tariff number	85369095
ETIM 9	EC001040

Approvals

Explanations Declaration of conformity

© Rittal 2025