


# Rittal – The System.

Faster – better – everywhere.



## SV 9661.230

## PE/PEN Combination Angle, E-Cu

State: 2026-02-09 (Source: [rittal.com/ca-en](https://rittal.com/ca-en))



FRIEDHELM LOH GROUP



# SV 9661.230 - PE/PEN Combination Angle, E-Cu for PE/PEN combinations

The PE/PEN combination, comprising busbars, combination angles and baying brackets, supports type-tested configurations as per IEC 61 439-1.

## Features

Model No.	SV 9661.230
Product description	The PE/PEN combination, comprising busbars, combination angles and baying brackets, supports type-tested configurations as per IEC 61 439-1.
Benefits	The pre-assembled combination angles, baying brackets and the busbars individually cut to the enclosure width make for extremely time and cost-efficient assembly
Applications	Form 2-4 Others
Material	E-Cu
Supply includes	Assembly components
Approved short-circuit current capability	$lcw 30 kA$ , 1 sec.
Suitable for busbars	Busbar E-Cu with integral punchings
OUT_CROSS_SECTION_COL_SM	30 - 10 mm
Suitable for busbars	Width: 30 Height: 10 mm
Packaging unit	4 pc(s).
Net weight	2
Gross weight	2.177
Copper weight (kg per piece)	0.408
Customs tariff number	74198090
EAN	4028177546653

# Features

---

ETIM 9 EC000329

---

ECLASS 8.0 27400605

# Approvals

---

Explanations Declaration of conformity  
Declaration of conformity UK