

Rittal – The System.

Faster – better – everywhere.



SV 9676.520 Contact maker

State: 2026-05-10 (Source: rittal.com/ca-en)

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



SV 9676.520 - Contact maker for connection brackets

To connect connection brackets and connector kits with flat copper bars to Flat-PLS busbar systems, no drilling required.

Features

Model No.	SV 9676.520
Product description	For joining connection brackets to busbar systems.
Material	E-Cu
Supply includes	Assembly components
For Busbar width	100 mm
Rails per conductor	2
Note	<p>The screws included with the supply are used to secure the contacts to the busbars</p> <p>Screws for fixing the connecting bracket are not included with the supply</p> <p>The required screw length must be selected according to the busbar width W, i.e., $\text{Length} = W + \text{fastening measurement} + (\text{number of partial conductors} \times 10)$</p> <p>Number of screws per bracket: With 2 subconductors per conductor: 2 pc(s) and with 3 or 4 subconductors per conductor 4 pc(s).</p>
Suitable for busbar system	Flat-PLS
Mounting dimensions	40 mm
Packaging unit	1 pc(s).
Net weight	0.839 kg
Gross weight	0.868 kg
Copper weight (kg per piece)	0.72
Customs tariff number	74198090
ETIM 9	EC001900
ECLASS 8.0	27400613

Features

Product description

SV Contact maker E-Cu, WH: 100x20 mm, for 2 strands, (Flat-PLS)

Approvals

Explanations

Declaration of conformity

Declaration of conformity UK