

Rittal – The System.

Faster – better – everywhere.



SV 9677.920 Connection block

State: 2026-07-09 (Source: rittal.com/ca-en)

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



SV 9677.920 - Connection block

For connecting cables and laminated copper bars.

Features

| | |
|-------------------------------------|--|
| Model No. | SV 9677.920 |
| Product description | For connecting conductors or laminated copper bars. |
| Material | Carbon steel, zinc-plated E-Cu, tin-plated |
| Cable outlet | Top/bottom |
| Type of connection (electrical) | Ring terminal M12 |
| Rated current max. | 1,600 A |
| Dimensions | Width: 98 mm |
| Connection of round conductors | 240 mm ² |
| Suitable for busbars | Height: 10 mm |
| Packaging unit | 1 pc(s). |
| Net weight | 1.6 kg |
| Gross weight | 1.662 kg |
| Copper weight (kg per piece) | 1.471 |
| PCF/VE (cradle-to-gate) | 6.3 kg CO2 eq (Cat B) |
| Information regarding the PCF class | Category B: PCF value (cradle-to-gate) calculated approximately on the basis of the product weight and self-declared |
| Customs tariff number | 85369095 |
| ETIM 9 | EC002270 |
| ECLASS 8.0 | 27400613 |
| Product description | SV Connection block, 1600 A, 690 V, 1-pole, cable outlet top/bottom, round conductor connection 240 mm ² |

Approvals

Approvals

UL + C-UL (listed)

Explanations

Declaration of conformity

Declaration of conformity UK