

Rittal – The System.

Faster – better – everywhere.



VX 9680.025

Baying-enclosure system VX25

State: 2026-06-22 (Source: rittal.com/ca-en)

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



VX 9680.025 - Baying-enclosure system VX25 Isolator enclosure

Baying system for the distribution of electrical power with slimline fuse-switch disconnectors (from ABB or Jean Müller).



Features

Model No.	VX 9680.025
Material	Carbon steel, 1.5 mm
Surface finish	Enclosure frame: Dipcoat-primed Door, roof and rear panel: Dipcoat-primed, powder-coated on the outside, textured paint Base plates: Zinc-plated
Color	RAL 7035
Supply includes	Enclosure frame Door Roof plate Rear panel Base Plates Front Trim Panels Lock: 3 mm double-bit Compartment side panels Locating frame for isolators with fuses (brands ABB SlimLine/Jean Müller SASIL)

Features

Protection category IP to EN 60529	Up to IP 2X (depending on the panels)
Test specification	IEC 61 439-1/-2 IEC 61 641
Dimensions	Width: 1,000 mm Height: 2,200 mm Depth: 600 mm
Packaging unit	1 pc(s).
Net weight	135.2 kg
Gross weight	146.4 kg
PCF/VE (cradle-to-gate)	333.1 kg CO2 eq (Cat B)
Information regarding the PCF class	Category B: PCF value (cradle-to-gate) calculated approximately on the basis of the product weight and self-declared
Customs tariff number	94032080
ETIM 9	EC000261
ECLASS 8.0	27180101
Product description	VX Fuse-switch disconnecter enclosure, WHD: 1000x2200x600 mm, sheet steel

Approvals

Certificates	Surface finish
Explanations	Declaration of conformity