Rittal – The System.

Faster – better – everywhere.





CS 9781.666 CS Toptec, bayable

State: 2025-11-01 (Source: rittal.com/ca-en)



CS 9781.666 - CS Toptec, bayable

Bayable, double-walled outdoor housing with 100 mm base, door, rear panel, and seamlessly bayable weatherproof roof. The complete enclosure frame is available for efficient and flexible interior fitting.







Features

Model No.	CS 9781.666
Version	For baying
	Without cut-out
Material	Housing frame: Stainless steel 1.4301 (AISI 304)
	Enclosure panels and base/plinth panels: Aluminum, AlMg3
	Rain canopy: Aluminum
Surface finish	Powder-coated
	UV-resistant pure polyester
Color	RAL 7035
Supply includes	Bayable, double-walled outdoor housing
	Enclosure frame with 25 mm system perforation in roof and base
	frames as well as vertical profiles with 2 mounting levels
	Front door with door stay, swing lever handle and semi-cylinder, lock
	BJ20027
	Rear panel
	Rain canopy
	Base/plinth with screw-fastened flange plates and screw-fastened
	trim panels front and rear
	Door hinged on the right, may be swapped to the left

© Rittal 2025

Features

Dimensions	Width: 600 mm Height: 1,600 mm Depth: 600 mm
Dimensions	Overall height: 1,745 mm Rain canopy height: 45 mm Height of base/plinth: 100 mm
Number of doors	1
Lock	Lock version: 4-point locking system No. of locks: 1 Lock Insert: BJ20027
Gland plate	Size: 2 Qty.: 2
Protection category IP to IEC 60 529	IP 55
Protection category NEMA	NEMA 3R NEMA 12
IK code	IK10
Note	All enclosure panels are double wall and grounded (external wall to internal wall) For the assembly of an enclosure, side panels for CS Toptec, bayable are required
Packaging unit	1 pc(s).
Net weight	55
Gross weight	65
EAN	4028177986138
ETIM 9	EC000261
ETIM 8	EC000261
ECLASS 8.0	27180101

Approvals

© Rittal 2025 3

Approvals

Explanations

Declaration of conformity

© Rittal 2025