Rittal – The System.

Faster – better – everywhere.





CS 9782.868 CS Toptec, bayable

State: 2025-09-08 (Source: rittal.com/ca-en)



CS 9782.868 - CS Toptec, bayable

Bayable, double-walled outdoor housing with 100 mm base, door, rear panel, and seamlessly bayable weatherproof roof. The complete enclosure frame is available for efficient and flexible interior fitting. The housing is prepared for the installation of a wall-mounted cooling unit Blue e+ Outdoor.







Features

CS 9782.868	
For baying	
With cut-out for outdoor climate control unit 5118.21 BTU/h	
Housing frame: Stainless steel 1.4301 (AISI 304)	
Enclosure panels and base/plinth panels: Aluminum, AlMg3	
Rain canopy: Aluminum	
Powder-coated	
UV-resistant pure polyester	
RAL 7035	
Bayable, double-walled outdoor housing	
Enclosure frame with 25 mm system perforation in roof and base	
frames as well as vertical profiles with 2 mounting levels	
Front door with door stay, swing lever handle and semi-cylinder, lock BJ20027 Rear panel Rain canopy Base/plinth with screw-fastened flange plates and screw-fastened	
	trim panels front and rear

© Rittal 2025

Features

Width: 800 mm Height: 1,600 mm Depth: 800 mm
Overall height: 1,745 mm Rain canopy height: 45 mm Height of base/plinth: 100 mm
1
Lock version: 3-point locking No. of locks: 1 Lock Insert: BJ20027
Size: 2 Qty.: 2
IP 55
NEMA 3R NEMA 12
IK10
All enclosure panels are double wall and grounded (external wall to internal wall) For the assembly of an enclosure, side panels for CS Toptec, bayable are required
To close the cutout, a climate control unit or adapter plate is needed
1 pc(s).
75
75.5
4028177986183
EC000261
EC000261
27180101

© Rittal 2025 3

Approvals

Explanations

Declaration of conformity

© Rittal 2025