## Rittal – The System.

Faster – better – everywhere.





# VX 1182.095 VX IT Open

State: 05/12/2025 (Source: rittal.com/com-en)



## VX 1182.095 - VX IT Open

VX IT standard version, without front and rear door. Usable either as an open 482.6 mm (19") frame in a secure environment or as the basis for fast configurations in the Rittal RiPanel configuration system using existing accessories (such as doors and side panels) from the Rittal modular range.







#### **Features**

Model No.	VX 1182.095	
Design	VX enclosure frame with roof plate without front and rear door Vented without side panels	
Surface finish	Enclosure frame: Dipcoat-primed Interior installation: Spray-finished	
General colour	RAL 7035	
Colour	Enclosure frame and roof: RAL 7035 Interior installation: RAL 9005	

© Rittal 2025

## Features

Supply includes	Enclosure frame Mounting angles, 482.6 mm (19") Spacers, height 50 mm, to raise a cover plate above the fan cut-out in the roof plate, for passive cooling (supplied loose). Not required for variants without a cut-out.  12 x 482.6 mm (19") fastener, 1 U, conductive (supplied loose) 25 multi-tooth screws, conductive (supplied loose) IPPC pallet Roof plate, multi-piece, with side cable entry in the depth, double-sided, prepared for fan mounting plate
Dimensions	Width: 800 mm Height: 2,000 mm Depth: 1,000 mm
Units	42 U
Free mounting space to the 482.6 mm (19") level, front/rear	87 mm / 193 mm
Mounting position of the 482.6 mm (19") level	front and rear
Distance between levels as delivered	720 mm
482.6 mm (19") attachment	on depth stays, screw-fastened at the top and bottom
Design	Standard
Roof design	multi-piece, with side cable entry in the depth, double-sided, prepared for fan mounting plate
Mounting angle design	482.6 mm (19") mounting angles, standard in the VX IT
Base design	Open
482.6 mm (19") level(s) version	front and rear
Load capacity	15,000 N
Max. load capacity (static) per enclosure to UL 2416	12,000 N
Basic material	Sheet steel
Packs of	1 pc(s).

© Rittal 2025 3

## Features

Net weight	67	
Gross weight	69	
EAN	4028177973312	
ETIM 9	EC002499	
ETIM 8	EC002499	
ECLASS 8.0	27180207	

# **Approvals**

Explanations	Manufacturer's declaration
	Declaration of conformity