Rittal – The System.

Faster – better – everywhere.



# SZ 2411.671

# Cable gland, polyamide

State: 23/11/2026 (Source: www.rittal.com/com-en)

# SZ 2411.671 - Cable gland, polyamide

Integrated clamping membranes ensure reliable tightening and strain relief to protect the cables.

## Features

| | |
|---|---|
| Model No. | SZ 2411.671 |
| Benefits | Because the gland and lock nut are sold together in a single pack, this saves additional ordering and storage.<br>Clamping membranes for even tightening and strain relief to protect the cables |
| Material | Polyamide 6<br>Seal: CR/NBR |
| Colour | RAL 7035 |
| IP protection category to IEC 60 529 | IP 68 (5 bar, 30 min) |
| Dimensions | Height: 53 mm |
| Thread | M63 x 1.5 |
| Thread length | 18 mm |
| Min. cable diameter | 34 mm |
| Max. cable diameter | 44 mm |
| Operating temperature range | -30 °C...100 °C |
| torque | 25 Nm |
| Width across flats | 65 mm |
| Dimensions | Thread: M63 x 1.5<br>Thread length: 18 mm |
| Type rating to 508A | Type 1<br>Type 4<br>Type 4X<br>Type 12<br>Type 13 |
| Packs of | 3 pc(s). |

© Rittal 2026

# Features

| | |
|---|---|
| Net weight | 0.372 kg |
| Gross weight | 0.375 kg |
| Customs tariff number | 39269097 |
| ETIM 9 | EC000441 |
| ETIM 8 | EC000441 |
| ECLASS 8.0 | 27149109 |
| Product description | SZ Cable gland, polyamide, size: M63x1,5, for cables ø 34-44 mm |

# Approvals

| | |
|---|---|
| Approvals | CSA + CSAus<br>UL + C-UL (listed)<br>VDE |
| Explanations | Declaration of conformity<br>Declaration of conformity UK |