

Faster – better – everywhere.





SZ 2482.300 Mounting frame, interface flap, modular

CLIMATE CONTROL

IT INFRASTRUCTURE SOFTWARE & SERVICES

State: 15/08/2025 (Source: rittal.com/com-en)

POWER DISTRIBUTION



FRIEDHELM LOH GROUP

ENCLOSURES

SZ 2482.300 - Mounting frame, interface flap, modular

Suitable for universal use, for rapid access to interfaces and sockets, the affected enclosure remains closed.

Features

Model No.	SZ 2482.300
Design	Mounting frame, single, with plastic flap (semi-transparent)
Product description	For universal use in all situations where rapid access to interfaces and sockets is needed. The affected enclosure remains closed and is therefore protected from ambient influences and unauthorised access.
Function principle	The mounting frame has a flap which snaps into position in various stages at opening angles of 90 to 180°. A snap fastener ensures reliable sealing. This may be locked if required.
Material	Lock: Polycarbonate Mounting frame, refined die-cast zinc Plastic flap: Polycarbonate (semi-transparent)
Surface finish	Mounting frame: Matt nickel-plated
Colour	Lock: RAL 7024 Screw terminals: yellow (RAL 1016)
Mounting cut-out	Cut-out width: 52 mm Cut-out height: 91 mm
Installation options	In small and compact enclosures as a programming interface for controllers In IT and industrial distributors as maintenance access for networks In PC enclosures and console systems for the temporary connection of additional equipment in mobile Industrial Workstations for rapid connection to existing network structures In command panel systems for programming and maintenance of integral components.

Features

DimensionsWidth: 65 mm Height: 120 mmIP protection category to IEC 60 529IP 65 with sealed flap and proper assembly 9 for sealed flap and proper assemblyPacks of1 pc(s).Net weight0.199Gross weight0.208Customs tariff number85369095EAN4028177311695ETIM 9EC002625ETIM 8EC002625ETIM 8EC002625ECLASS 8.027189234		
529Packs of1 pc(s).Net weight0.199Gross weight0.208Customs tariff number85369095EAN4028177311695ETIM 9EC002625ETIM 8EC002625	Dimensions	
Net weight0.199Gross weight0.208Customs tariff number85369095EAN4028177311695ETIM 9EC002625ETIM 8EC002625		IP 65 with sealed flap and proper assembly
Gross weight0.208Customs tariff number85369095EAN4028177311695ETIM 9EC002625ETIM 8EC002625	Packs of	1 pc(s).
Customs tariff number 85369095 EAN 4028177311695 ETIM 9 EC002625 ETIM 8 EC002625	Net weight	0.199
EAN 4028177311695 ETIM 9 EC002625 ETIM 8 EC002625	Gross weight	0.208
ETIM 9 EC002625 ETIM 8 EC002625	Customs tariff number	85369095
ETIM 8 EC002625	EAN	4028177311695
	ETIM 9	EC002625
ECLASS 8.0 27189234	ETIM 8	EC002625
	ECLASS 8.0	27189234

Approvals

Explanations

Declaration of conformity