

**Rittal – The System.**

Faster – better – everywhere.



# SK 3301.920 Overflow valve

State: 02/07/2026 (Source: [rittal.com/com-en](http://rittal.com/com-en))

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# SK 3301.920 - Overflow valve

Pressostat for use in the water cycle between the recooling system and the air/water heat exchanger. It prevents an increase in pump pressure in the recooling system against the closed magnetic valve of the air/water heat exchanger outside of the cooling cycle.

## Features

|                               |   |
|-------------------------------|---|
| Model No.                     | SK 3301.920   |
| Product description           | Pressostat for use in the water cycle between the recooling system and the air/water heat exchanger. It prevents an increase in pump pressure in the recooling system against the closed magnetic valve of the air/water heat exchanger outside of the cooling cycle. |
| Material                      | Brass   |
| Valve design                  | 1" bypass valve   |
| OUT_PRESSURE_ADJUSTMENT_RANGE | 2 - 12 bar  |
| Packs of                      | 1 pc(s).  |
| Net weight                    | 1.019 kg  |
| Gross weight                  | 1.046 kg  |
| Customs tariff number         | 84818059  |
| ETIM 9                        | EC000855  |
| ETIM 8                        | EC000855  |
| ECLASS 8.0                    | 27180704  |
| Product description           | SK Bypass valve 1", for use with recooling systems and air/water heat exchangers, 2-12 bar, presetting 3 bar  |