

**Rittal – The System.**

Faster – better – everywhere.



# SV 3572.005

## Laminated copper bars

State: 18/06/2026 (Source: [rittal.com/com-en](http://rittal.com/com-en))

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# SV 3572.005 - Laminated copper bars

Cu lamina made of high-purity electrolyte copper 720, length: 2000 mm/bar.



## Features

|                                                |                                                                                                                                                                                                                              |
|------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Model No.                                      | SV 3572.005                                                                                                                                                                                                                  |
| Material                                       | Cu lamina High-purity electrolytic copper F20<br>Insulation: Highly resistant vinyl compound, elongation 370%,<br>temperature: -30 °C...+105 °C, fire protection corresponding to UL-94<br>V0, dielectric strength: 20 kV/mm |
| Length                                         | 2,000 mm                                                                                                                                                                                                                     |
| Rated current for temperature<br>increase 50 K | 770 A                                                                                                                                                                                                                        |
| Rated current for temperature<br>increase 30 K | 585 A                                                                                                                                                                                                                        |
| Rated current for temperature<br>increase 70 K | 920 A                                                                                                                                                                                                                        |

# Features

---

|                                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
|---------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Note                            | Construction = Number of lamina x lamina width x lamina thickness<br>May be cut individually to required length<br>The conductor temperature of the laminated copper bar is derived by adding the ambient temperature and the temperature increase together. Example: 3565.005 carrying 180 A, i.e. the temperature increases by 30 K. At an ambient temperature of 35 °C, this produces a resultant conductor temperature of 35 °C + 30 K = 65 °C. |
| Version – laminated flat copper | Number of lamina: 10<br>Membrane width: 24 mm<br>Membrane thickness: 1 mm                                                                                                                                                                                                                                                                                                                                                                           |
| Packs of                        | 1 pc(s).                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Net weight                      | 4.813 kg                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Gross weight                    | 4.94 kg                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Copper weight (kg per piece)    | 4.3                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Customs tariff number           | 85446010                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| ETIM 9                          | EC001522                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| ETIM 8                          | EC001522                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| ECLASS 8.0                      | 27370303                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Product description             | SV Laminated copper bar, WH: 24x10 mm, L: 2000 mm                                                                                                                                                                                                                                                                                                                                                                                                   |

---

# Approvals

---

|              |                                                           |
|--------------|-----------------------------------------------------------|
| Approvals    | UR + C-UR (recognized)                                    |
| Explanations | Declaration of conformity<br>Declaration of conformity UK |

---