Rittal – The System.

Faster – better – everywhere.



# DK 5302.006

# Air baffle plate

State: 31/10/2026 (Source: www.rittal.com/com-en)

# DK 5302.006 - Air baffle plate for VX IT 482.6 mm (19") mounting angles, dynamic

To separate the hot/cold zones within an enclosure with aisle containment or when using an LCP system.



## Features

| | |
|---|---|
| Model No. | DK 5302.006 |
| Product description | For selectively boosting the energy efficiency of a climate control system. |
| Benefits | Vertical brush strip for collision-free shielding with installed rail systems on the outer mounting level. |
| Applications | To separate the hot/cold zones within an enclosure with aisle containment or when using an LCP system. |
| Material | Sheet steel<br>Blanking panel: Plastic, UL 94-HB, halogen-free<br>Brush strip: Plastic, UL 94-HB |
| Surface finish | Spray-finished |
| Colour | RAL 9005 |
| Supply includes | 2 vertical trim panels<br>2 horizontal trim panels<br>4 brush strips<br>4 cellular PU foam pieces<br>Assembly parts |

# Features

| | |
|---|---|
| Assembly instruction | The vertical trim panels with brush strip may be fitted on both the front and rear 482.6 mm (19") mounting angles for partitioning.<br>The horizontal trim panels with brush strips can only be mounted on the front 482.6 mm (19") mounting angles.<br>482.6 mm (19") mounting cut-outs integrated within the partitioning areas may optionally be sealed with the supplied blanking panels, or used to install additional components or for cable routing. Please see the product-specific scope of supply. |
| To fit | Width: = 600 mm<br>Height: = 2,200 mm |
| Packs of | 1 pc(s). |
| Net weight | 2.32 kg |
| Gross weight | 2.92 kg |
| PCF per pack (cradle-to-gate) | 11.1 kg CO2 eq (Cat B) |
| Note on PCF category | Category B: PCF value (cradle-to-gate) based on the product weight, approximately calculated and self-declared |
| Customs tariff number | 73269098 |
| ETIM 9 | EC000331 |
| ECLASS 8.0 | 27189272 |
| Product description | Air baffle plate, for VX IT 19" mounting angles, dynamic, to separate the hot/cold zones within an enclosure with aisle containment or when using an LCP system. WxD: 600x2200 mm, RAL 9005 |