Rittal – The System.

Faster – better – everywhere.



# CX 6705.000

# CX pedestal

State: 05/11/2026 (Source: www.rittal.com/com-en)

# CX 6705.000 - CX pedestal

CX pedestals, four widths and two different depths provide the basis for every console solution. The AX lock plate ensures a uniform appearance, and two-part gland plates are included with the supply for simple cable routing.







## Features

| | |
|---|---|
| Model No. | CX 6705.000 |
| Design | Pedestal |
| Material | Enclosure: Sheet steel 1.5 mm<br>Door: Sheet steel, 2.0 mm, all-round foamed-in PU seal<br>Mounting plate: Sheet steel, 2.5 mm |
| Surface finish | Enclosure and door: Dipcoat primed, powder-coated on the outside, textured paint<br>Mounting plate: Zinc-plated |
| Colour | RAL 7035 |
| Supply includes | Enclosure open at top<br>Door or double-door at front, with 3-point locking system<br>Mounting plate<br>Gland plates<br>Lock: 3 mm double-bit |
| Dimensions | Width: 800 mm<br>Height: 675 mm<br>Depth: 500 mm |

© Rittal 2026

# Features

| | |
|---|---|
| Dimensions mounting plate (W x H) | 720 mm x 625 mm |
| Number of doors | 1 |
| Door opening angle | 130° |
| IK Code | IK10 |
| Note | A cover plate is required to seal the pedestal<br>A desk unit and desk unit cover plate are required for 2-part console assembly<br>A desk unit and console are required for 3-part console assembly. |
| IP protection category to IEC 60 529 | IP 55 |
| Protection category NEMA | NEMA 1<br>NEMA 12 |
| Basic material | Sheet steel |
| Number of locks | 1 |
| Lock version | 3-point lock system |
| Lock insert | 3 mm double-bit |
| Lock | Lock version: 3-point lock system<br>Number of locks: 1<br>Lock insert: 3 mm double-bit |
| Packs of | 1 pc(s). |
| Net weight | 40 kg |
| Gross weight | 42.875 kg |
| Customs tariff number | 94032080 |
| ETIM 9 | EC000784 |
| ETIM 8 | EC000784 |
| ECLASS 8.0 | 27180504 |
| Product description | CX console system, pedestal, WxHxD: 800x675x500 mm, sheet steel |

# Approvals

| | |
|---|---|
| Approvals | UL + C-UL (listed) |
| Explanations | Declaration of conformity |

© Rittal 2026