

# Rittal – The System.

Faster – better – everywhere.



## DK 7111.900 Cable shunting ring

State: 15/05/2026 (Source: [rittal.com/com-en](http://rittal.com/com-en))

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# DK 7111.900 - Cable shunting ring

For flexible, system-compatible cable routing at the side of the 482.6 mm (19") mounting angles.



## Features

Model No.	DK 7111.900
Product description	For flexible, system-compatible cable routing at the side of the 482.6 mm (19") mounting angles.
Material	Steel
Surface finish	Zinc-plated
Supply includes	Assembly parts
Dimensions	Height: 85 mm Depth: 125 mm
Packs of	10 pc(s).
Net weight	0.95 kg
Gross weight	0.991 kg
PCF per pack (cradle-to-gate)	5.3 kg CO2 eq (Cat B)
Note on PCF category	Category B: PCF value (cradle-to-gate) based on the product weight, approximately calculated and self-declared
Customs tariff number	83024200
ETIM 9	EC000322
ECLASS 8.0	27400604
Product description	DK Cable shunting ring, TxH: 125x85 mm

# Tender text

Cable shunting ring, zinc-plated, passivated

The zinc-plated, passivated cable shunting rings, made from HxD 85 x 125 mm steel sheet, are fitted on telecommunication system strips or direct in telecommunication distribution enclosures and support the flexible, system-compatible cable routing.

Material: Sheet steel, zinc-plated, passivated

Dimensions: HxD 85 x 125 mm

Packs of 10