

Rittal – The System.

Faster – better – everywhere.



RX 9360.102 RiLineX end module set

State: 10/06/2026 (Source: rittal.com/com-en)

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



RX 9360.102 - RiLineX end module set for basic module

RiLineX end module set, 3-pole, for the modular RiLineX board, suitable for top mounting. This set forms board ends on the left and right, including all-round contact hazard protection. Devices may be attached to the end modules. Using the end module set Plus provides 36 mm of additional installation space on the RiLineX board.



Features

Model No.	RX 9360.102
Benefits	Scalable system lengths with basic modules Simple assembly Scalable rated currents thanks to variable busbar cross-sections Tested short-circuit resistance up to 65 kA Suitable for applications up to 1000 V AC and up to 1500 V DC Extensive range of system accessories Contact hazard protection up to IP 2XB, upgradable to IP 3X Tested and certified to IEC and UL Simple extension and baying
Material	Polyamide (PA 6) Fire protection corresponding to UL 94
Colour	RAL 35745
Supply includes	Board end element, left Board end element, right Assembly parts
To fit Model No.	9360.110 9360.120 9360.150
Number of poles	3-pole
Packs of	2 pc(s).

Features

Net weight	0.99 kg
Gross weight	1.146 kg
Customs tariff number	85369010
Product description	RiLineX end module set for the 3-pole modular RiLineX board. This set forms board ends on the left and right, including all-round contact hazard protection. This end module set is suitable for top mounting. The supply includes one left-hand end module and one right-hand end module, plus assembly parts.

Tender text

RiLineX end module set plus, for the modular RiLineX board.

RiLineX end module set plus, for the modular RiLineX board.

This set forms board ends on the left and right, including all-round contact hazard protection.

Devices may be attached to the end modules.

Using the end module set Plus provides 36 mm of additional installation space on the RiLineX board.

One of these is required for each modularly assembled RiLineX board system.

For voltages up to 1000 V AC and 1500 V DC.

Tested short-circuit resistance up to 65 kA.

IEC and UL approved.

Product information

Number of poles: 3

Busbar dimensions: 15/20/30 mm x 5/10 mm

Rated current max.: 550/800 A

Dimensions: 105 mm x 246 mm x 49,2 mm (WxHxD)

Manufacturer: Rittal GmbH & Co. KG

Type: 9360102