

Rittal – The System.

Faster – better – everywhere.



RX 9365.013

RiLineX baying connector

State: 22/05/2026 (Source: rittal.com/com-en)

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



RX 9365.013 - RiLineX baying connector for busbars

Long busbar connector for the enclosure-to-enclosure baying set, for connecting modular RiLineX boards. The 3-pole baying set (9360104) is additionally required.



Features

| | |
|-------------------------------|---|
| Model No. | RX 9365.013 |
| Material | Upper part: Sheet steel, zinc-plated Contact plate: E-Cu, tin-plated |
| Rated current (max.) | 800 A |
| Dimensions | Width: 130 mm |
| To fit busbars | 15 x 5/10 20 x 5/10 30 x 5/10 |
| Packs of | 3 pc(s). |
| Net weight | 1.5 kg |
| Gross weight | 1.593 kg |
| Copper weight (kg per piece) | 0.99 |
| PCF per pack (cradle-to-gate) | 8.7 |
| Customs tariff number | 73269098 |
| ETIM 9 | EC002622 |
| Product description | Long busbar connector for the enclosure-to-enclosure baying set, for connecting modular RiLineX boards. The 3-pole baying set (9360104) is additionally required. For E-Cu 15x5-30x10 mm, L: 130 mm |

Approvals

| | |
|--------------|--|
| Approvals | UL + C-UL (listed) |
| Explanations | Declaration of conformity PCF-declaration |

Tender text

RiLineX Anreihverbinder für Sammelschienen (lang)

Long busbar connector for the enclosure-to-enclosure baying set, for connecting modular RiLineX boards.

The baying set (9360104) is additionally required.

For voltages up to 1000 V AC and 1500 V DC.

Tested short-circuit resistance up to 65 kA.

IEC and UL approved.

Product information

Number of poles: 3

Busbar dimensions: 15/20/30 mm x 5/10 mm

Rated current max.: 550/800 A

Manufacturer: Rittal GmbH & Co. KG

Type: 9365013