


# Rittal – The System.

Faster – better – everywhere.



## KEL 9407.600 Ex enclosures

State: 04/04/2026 (Source: [rittal.com/com-en](http://rittal.com/com-en))

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# KEL 9407.600 - Ex enclosures stainless steel, empty enclosure with hinged door

Ex enclosure with hinged door, stainless steel



## Features

|                 |   |
|-----------------|---|
| Model No.       | KEL 9407.600  |
| Design          | Ex enclosures   |
| Applications    | Zone 1 and 2 or 21 and 22 to 2014/34/EC<br>Ambient temperature range: -30 °C...+80 °C<br>The specified temperatures may be limited by the installed equipment<br>Explosion protection category to EN 60 079: Equipment protection thanks to increased safety (Ex e), equipment protection thanks to enclosure (Ex tb) |
| Material        | Enclosure: Stainless steel 1.4301 (AISI 304)<br>Door: Stainless steel 1.4301 (AISI 304), all-round foamed-in silicone seal<br>Mounting plate: Sheet steel   |
| Surface finish  | Enclosure: Brushed, grain 400, peak-to-valley height < 0.8 µm<br>Mounting plate: Zinc-plated  |
| Supply includes | Enclosure<br>Door<br>Mounting plate   |

# Features

---

|                                     |  |
|-------------------------------------|--|
| Dimensions                          | Width: 760 mm<br>Height: 760 mm<br>Depth: 300 mm   |
| Dimensions mounting plate (W x H)   | 704 mm x 730 mm  |
| Certificate IEC EX PTB 09.0035U     | Yes  |
| Certificate PTB 02 ATEX 1082U       | Yes  |
| Basic material                      | Stainless steel 1.4301 (AISI 304)  |
| Lock                                | Lock version: Cam<br>Number of locks: 2<br>Lock insert: 3 mm double-bit  |
| IP protection category to IEC 60529 | IP 66  |
| Protection category NEMA            | NEMA 4X  |
| Type rating to UL 50E               | Type 1<br>Type 4<br>Type 4X<br>Type 12   |
| Packs of                            | 1 pc(s).   |
| Net weight                          | 39.9 kg  |
| Gross weight                        | 42 kg  |
| Customs tariff number               | 94032080   |
| ETIM 9                              | EC002503   |
| ECLASS 8.0                          | 27180502   |
| Product description                 | KEL Ex enclosure, WHD: 760x760x300 mm, Stainless steel 1.4301, with mounting plate, Empty enclosure with hinged door |

---

# Approvals

# Approvals

---

|           |  |
|-----------|--|
| Approvals | ATEX<br>ATEX QA<br>CQC-CCC<br>IECEX<br>IECEX QAR<br>UL + C-UL (listed) |
|-----------|--|

---

|              |                           |
|--------------|---------------------------|
| Explanations | Attestation of Conformity |
|--------------|---------------------------|