## Rittal – The System.

Faster – better – everywhere.





# CS 9791.015 Outdoor wall-mounted enclosures

State: 19/11/2025 (Source: rittal.com/com-en)



## CS 9791.015 - Outdoor wall-mounted enclosures

Outdoor enclosures for wall or pole mounting. Enclosure-within-an-enclosure concept, outer enclosure with cut-out at the bottom and integrated louvres on the rear panel and side panels for ventilation.







## **Features**

Model No.	CS 9791.015
Product description	Outdoor enclosures for wall or pole mounting. Enclosure-within-an- enclosure concept, outer enclosure with cut-out in the bottom and integrated louvres on the rear panel and side panels for ventilation.
Material	Enclosure and mounting plate: Aluminium, AlMg3
	Door, inner enclosure: Stainless steel 1.4301 (AISI 304)
Surface finish	Enclosure: Powder-coated, UV-resistant pure polyester
Colour	RAL 7035
Supply includes	Double-walled outdoor enclosure, fully preconfigured
	Inner enclosure with mounting plate, gland plate and security lock
	Mounting bracket for enclosure internal thermostat or hygrostat
	Outer enclosure with designer cover and security lock 3524 E
	2 C rails on the rear panel
Dimensions	Width: 370 mm
	Height: 522 mm
	Depth: 210 mm

## Features

Clearances	Clearance width: 280 mm
	Clearance height: 380 mm
	Clearance depth: 145 mm
Dimensions mounting plate (W x H)	270 mm x 380 mm
Inner enclosure	Width: 300 mm
	Height: 400 mm
	Depth: 170 mm
Lock	Lock version: Cam
	Number of locks: 1
IP protection category to IEC 60 529	IP 55
Note	Extended delivery times.
Basic material	Aluminium
Packs of	1 pc(s).
Net weight	8.048
Gross weight	8.472
Customs tariff number	94032080
EAN	4028177193697
ETIM 9	EC000261
ECLASS 8.0	27180101

# Approvals

Explanations	Declaration of conformity
	Declaration of conformity UK

## Tender text

#### Outdoor wall-mounted enclosure

Dual-shell outdoor aluminium enclosure for pole or wall mounting, consists of an outdoor enclosure with louver ventilation, security lock and a lockable interior enclosure with mounting plate.

#### Interior enclosure:

Body: 1.5 mm aluminium, folded and welded from a single piece with protection channel around the door opening. Screwed on gland plate fitted at top (W x D = 97.5 x 65.5 mm) and bottom (W x D = 182 x 52 mm). Thermostat mounting holder fitted at top left.

Door: 1,5 mm stainless steelt, mounted, with foamed-in sealer and screwed on hinges, 180° opening angle, cam lock with security lock

Mounting plate: 2 mm aluminium

#### Outer enclosure:

Enclosure with removable cover and security lock design. Ventilation louvers in upper left, right and rear sections; rows of ventilation holes in the left and right side of the base. Screwed on gland plate at the bottom.

Two C-rails screwed on at the rear for mounting a pole attachment. Enclosure cover with recessed handle.

#### Material

Interior enclosure, outer enclosure and mounting plate: Aluminium AIMg3

#### Surface:

Interior enclosure and outer enclosure: Powder-coated

in RAL 7035

Mounting plate: zinc-plated, passivated

#### Dimensions:

Interior enclosure: W x H x D: 300 x 400 x 170 mm Outer enclosure: W x H x D: 370 x 522.5 x 210 mm

### Protection category:

IP 55 to EN 60 529/10.91