Rittal – The System.

Faster – better – everywhere.

RX 9363.000

RiLineX Fuse-switch disconnector

Stat: 06-07-2025 (Kilde: rittal.com/dk-da)

RX 9363.000 - RiLineX Fuse-switch disconnector

RiLineX NH fuse-switch disconnector in size 00 for mounting plates. The cover can be locked and prepared for a lead seal. It also has visual fuse monitoring. Integrated measuring points on the cover ensure safe voltage testing. NH fuse-switch disconnectors have a park position to make maintenance easier. Size M8 screw terminal connection.

Funktioner

Best.nr.	RX 9363.000
Udgave	Til montageplader
Fordele	Cover: can be locked and prepared for a lead seal Voltage test through separate opening Snap-on mounting up to 250 A and simple adjustment to busbar thickness 5/10 mm Tool-free changeover of the cable outlet Park position for simpler maintenance work High rated voltage 800 V ready All variants also available with electronic fuse monitoring
Materiale	Polyamid (PA 6) Brandegenskaber iht. UL 94 Kontaktbaner: Elektrolytkobber, forsølvet
Farve	RAL 9005 RAL 35745
for mounting plate assembly	Ja
Ledningsafgang	foroven/forneden

Funktioner

Tilslutningstype (elektrisk)	Skrue M8
Rated insulation voltage	1.000 kV
Mærkestrøm maks.	160 A
Mærkedriftsspænding	690 V AC
Til NH-størrelse	00
Test specification	IEC/DIN EN 60 947-3 DIN EN 60 269-2 (sikringsindsatse)
Dimensioner	Bredde: 106 mm Højde: 194 mm Dybde: 84 mm
Driftstemperatur	-5 °C...35 °C
Opbevaringstemperatur	-25 °C...70 °C
Antal poler	3-polet
Utilisation category	AC-23B (400 V/100 A) AC-22B (500 V/100 A) AC-21B (690 V/100 A) DC-22B (250 V/100 A)
Forureningsgrad	3
Kapslingsklasse IP iht. IEC 60 529	IP 2XB
Pakkestørrelse	1 stk.
Nettovægt	0.755
Bruttovægt	0.785
Kobberandel (kg/styk)	0.18
Toldtarifnummer	85369095
ETIM 9	EC001040

Godkendelser.

Godkendelser.

Forklaringer.	Overensstemmelseserklæring