Rittal – The System.

Faster – better – everywhere.

# SR 2332.235

# Swing frame, large, with trim panel

State: 11/02/2026 (Source: rittal.com/gr-en)

ENCLOSURES POWER DISTRIBUTION CLIMATE CONTROL IT INFRASTRUCTURE SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

# SR 2332.235 - Swing frame, large, with trim panel for TS, VX SE 800 mm wide enclosures

For 800 mm wide enclosures, 22 - 45 U, with trim panel, for mounting 482.6 mm (19") equipment.

## Features

| | |
|---|---|
| Model No. | SR 2332.235 |
| Design | 482.6 mm (19") level, side |
| Product description | For mounting 482.6 mm (19˝) equipment. |
| Material | Sheet steel |
| Surface finish | Frame: Zinc-plated<br>Trim panel: Spray-finished |
| Colour | RAL 7035 |
| Supply includes | Locking rod system with double-bit lock insert<br>Material for attaching |
| Installation options | In the TS/SE with 130° or 180° opening angle, depending on the chosen mounting kit |
| Assembly instruction | Depending on the mounting situation, TS punched sections with mounting flanges 23 x 73 mm or 17 x 73 mm are required |

# Features

| | |
|---|---|
| Note | For further installation options, see "Technical details"<br>For two-door enclosures TS, SE with a height of 1800 or 2200 mm the next-smallest swing frame must be installed, due to collision with the lock |
| To fit | Enclosure type: TS<br>VX SE<br>Width: = 800 mm<br>Height: ≥ 1,600 mm |
| Units | 31 U |
| To fit enclosure type | TS<br>VX SE |
| Packs of | 1 pc(s). |
| Net weight | 16.57 |
| Gross weight | 17 |
| Customs tariff number | 94039910 |
| EAN | 4028177165137 |
| ETIM 9 | EC002620 |
| ETIM 8 | EC002620 |
| ECLASS 8.0 | 27189261 |

# Tender text

Large swing frame for network enclosure
Large swing frame for network enclosure
31 U can be used for accommodating 482.6 mm (19") equipment.
Torsionally stiff frame, welded from rectangular tube and triple folded support section. Load capacity up to 1500 N when standard hinges are used. Distance from inside edge of door to front edge of swing frame 100 mm, may be installed deeper on a pitch pattern of 25 mm. The swing frame must be fitted to the left / to the right depending on the installation depth of the equipment. Installation position of equipment mounted to the side.
Material: sheet steel
Surface finish: RAL 7035
for enclosure width: W: 800 mm