Rittal – The System.

Faster – better – everywhere.





SK 3238.824 Blue e+ filter fan

State: 17/11/2025 (Source: rittal.com/gr-en)




SK 3238.824 - Blue e+ filter fan EMC

Complete fan unit with EMC shielding for tool-free mounting on surfaces. Air throughput from $20 - 900 \, \text{m}^3\text{/h}$







Features

SK 3238.824		
wall-mounted EMC		
EMC fan-and-filter units offer a high shielding/attenuation effect and meet requirement category 2 to EN 61587-3.		
Easy filter changes, thanks to a new opening mechanism on the louvred grille Faster installation on the enclosure with optimised detent hooks Diagonal fan technology achieves more even and constant ventilation of the enclosure, thanks to improved pressure stability Tool-free assembly		
Plastic		
RAL 7035		
Complete unit ready to install, including EMC filter mat		
Axial, DC motor		
With DC: 53 m³/h		

© Rittal 2025

Features

Air throughput with matching outlet filter including chopped-fibre filter	With DC: 40 m³/h		
Rated operating voltage	24 V (DC)		
Power consumption Pel	With DC: 5.7 W		
Rated current max.	With DC: 0.27 A		
Dimensions	Width: 148.5 mm Height: 148.5 mm Depth: 82.5 mm		
Installation depth	64 mm		
Mounting cut-out	Cut-out width: 124 mm Cut-out height: 124 mm		
IP protection category to IEC 60 529	IP 54 with chopped-fibre filter IP 56 with chopped-fibre filter and hose-proof hood		
Protection category NEMA	Type 12 with chopped-fibre filter Type 3, 3R, 4, 4X with chopped-fibre filter and hose-proof hood		
Pre-fuse	Miniature circuit-breaker/fuse: 2 A		
Note	To improve energy efficiency and extend the service life of the devices, we recommend the use of thermostats or temperature displays		
Operating temperature range	-15 °C55 °C		
Storage temperature range	-30 °C70 °C		
Noise level	With DC: 52 dB(A)		
Packs of	1 pc(s).		
Net weight	0.9		
Gross weight	0.92		
Customs tariff number	84145915		
EAN	4028177985544		
ETIM 9	EC000320		
ETIM 8	EC000320		

© Rittal 2025 3

Features

CLASS 8.0	27180716

Approvals

Approvals	30 - KC Korea
	UL + C-UL - FTTA UR + C-UR (recognized)
Explanations	Declaration of conformity

© Rittal 2025