

**Rittal – The System.**

Faster – better – everywhere.



**SV 3515.000**

**PLS busbar connectors**

State: 13/05/2026 (Source: [rittal.com/gr-en](http://rittal.com/gr-en))

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# SV 3515.000 - PLS busbar connectors

For connecting PLS special busbars, no drilling required.



## Features

Model No.	SV 3515.000
Product description	For connecting the PLS special busbars, no drilling required.
Material	E-Cu
Surface finish	Nickel-plated
Rated current (max.)	1,368 A
To fit busbars	PLS 1600
To fit Model No.	9342.000 9342.004 9342.050
Connection type	Baying connection from enclosure to enclosure
Dimensions	Length: 150 mm
Packs of	3 pc(s).
Net weight	3.81 kg
Gross weight	4.015 kg
Copper weight (kg per piece)	1.27
Customs tariff number	85369010
ETIM 9	EC000713
ETIM 8	EC000713

# Features

---

ECLASS 8.0

27400606

---

Product description

SV Busbar connector, PLS 1600, bayed connection

# Approvals

---

Approvals

ABS

DNV

Lloyds Register

UL + C-UL (listed)

---

Explanations

Declaration of conformity

Declaration of conformity UK

# Tender text

PLS 1600 busbar connector

System

Rittal RiLine60

Description

PLS 1600 busbar connector for connecting the

PLS 1600 special busbar

Design

Baying connection from enclosure to enclosure

Material properties

E-Cu, nickel-plated

Screw M10

Tightening torque

20 Nm

Note

The use of cross members 9340240/230 is compulsory for UL 508A applications.