

Rittal – The System.

Faster – better – everywhere.



AS 4051.220

WT vibratory bowl feeder

State: 13/05/2026 (Source: rittal.com/gr-en)

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



AS 4051.220 - WT vibratory bowl feeder

WT 16 vibratory bowl feeder for guiding loose wire end ferrules with plastic collars for a cross-section of 0.5 mm² into the Wire Terminal WT C fully automated wire processing machine.



Features

| | |
|-----------------------|---|
| Model No. | AS 4051.220 |
| Benefits | Process reliability with the infeed of wire end ferrules Simple, fast changeover of consumable materials |
| Supply includes | WT 16 vibratory bowl feeder |
| Applications | For loose wire end ferrules with cross-section 0.5 mm ² |
| Note | The vibratory bowl feeders and the separation of single wire end ferrules are designed for the dimensional tolerances of Rittal wire end ferrules to DIN 46228-4:2019-02. If the wire end ferrules used exceed the defined dimension tolerances, it may be necessary to design/test a new bowl feeder and to adapt the wire end ferrule separation. |
| Standards | AEH DIN 46228 |
| To fit Model No. | 4051.205 4051.210 |
| Customs tariff number | 84799070 |