

Faster – better – everywhere.





PC 5366.150 PC enclosure system

POWER DISTRIBUTION >> CLIMATE CONTROL

State: 10/09/2025 (Source: rittal.com/gr-en)



IT INFRASTRUCTURE SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

ENCLOSURES

PC 5366.150 - PC enclosure system

Secure accommodation of all PC components, from monitors, to PCs, to keyboards. For ultimate ease of operation in a modern design. Perfect protection from humidity and dirt, temperature fluctuations and unauthorised access.



Features

Model No.	PC 5366.150
Design	with glazed door at the top, folding keyboard and component shelf
Product description	Secure accommodation of all PC components, from monitors, to PCs, to keyboards. For ultimate ease of operation in a modern design. Perfect protection from humidity and dirt, temperature fluctuations and unauthorised access.
Material	Enclosure, door, rear door, mounting compartment, supports: Sheet steel Handles, decorative trim panels: Plastic Door trim panels: Aluminium Viewing window: Single-pane safety glass
Surface finish	Enclosure and door: Dipcoat primed, powder-coated on the outside, textured paint
General colour	RAL 7035
Colour	Enclosure, door, decorative trim panels, supports: RAL 7035 Handle: RAL 7015 Monitor panel, door centre part: RAL 7015

Features

Supply includes	Enclosure, door, rear door
	Gland plates
	Glazed door, top
	Folding keyboard
	Component shelf
Dimensions	Width: 600 mm
	Height: 1,600 mm
	Depth: 636 mm
IP protection category to IEC 60 529	IP 55
Protection category NEMA	NEMA 12
Type rating to UL 50E	Туре 1
	Type 12
Max. keyboard dimensions	497 x 50 x 250 mm
(WxHxD)	497 x 60 x 200 mm
Basic material	Sheet steel
Packs of	1 pc(s).
Net weight	85.5
Gross weight	88
PCF per pack (cradle-to-gate)	373.4 kg CO2 eq (Cat B)
Note on PCF category	Category B: PCF value (cradle-to-gate) based on the product weight, approximately calculated and self-declared
EAN	4028177959460
ETIM 9	EC002502
ECLASS 8.0	27180501

Approvals

Approvals	UL + C-UL (listed)
Certificates	Surface finish

Approvals

Explanations

Declaration of conformity Declaration of conformity UK

Tender text

PC Enclosure with glazed door, folding keyboard and component shelf

Enclosure for stand-alone siting, consisting of solid body, glazed door at the top, keyboard drawer, component shelf, bottom door, rear door and welded base assembly. Enclosure body with profiled mounting angles at the front and rear on sidewalls and roof. System slots on a 25 mm pitch pattern, all around, for individual interior installation and two pairs of mounting angles for space-saving system installation. Glazed door, top: With support frame latched from the inside, right hinge vertical decorative trim panels, pane with screen-printed mask Component shelf for monitor: Perforated, fixed Folding keyboard: Housing with mouse support and cut-out in the rear. Trim panel hinged at the bottom, with 2 retaining cords, with lock insert no. 3524 max. keyboard dimensions (WxHxD): 497x50x250 mm or 497x60x200 mm Keyboard support with mousepad extension piece Nylon loop for keyboard with unlocking device for glazed door, top Bottom door: Vertical bars with locking rod and double-bit insert hinged on right-hand side Door resp. installation plate folded Rear door: With locking rod and double bit insert

hinged on right-hand side With gland plates, divided Material: Enclosure, door, rear door, mounting compartment, supports: sheet steel Handles, decorative trim panels: plastic Door trim panels: Aluminium Viewing window: single-pane safety glass Gland plate : sheet steel, galvanized Surface finish: Enclosure and door: dipcoat primed, powder coated outsidee, textured paint Colour: Enclosure, door, decorative trim panels, supports: RAL 7035 Handles: RAL 7015 Monitor panel, door center part: RAL 7015 Protection class: IP to IEC 60 529: IP55 NEMA: NEMA 12 Dimensions WHD: 600 x 1600 x 636 mm Model No: 5366150 Manufacturer: Rittal GmbH & Co.KG