

Rittal – The System.

Faster – better – everywhere.



DK 7010.200 Sensors

State: 05/09/2026 (Source: www.rittal.com/gr-en)

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



DK 7010.200 - Sensors for CMC III, PDU, LCP, IoT interface

The smoke detector monitors the air in the enclosure for smoke particles.

Features

Model No.	DK 7010.200
Design	Smoke alarm
Benefits	Fast connection and automatic detection via plug & play Power is supplied via the CAN-BUS interface.
Applications	Enclosure monitoring in IT, industry and facility management Monitoring of enclosures, rooms and containers in the IT environment
Function principle	Settings can be made via the CMC III processing unit or IoT interface The CMC III smoke detector is mounted in the top of the enclosure. The sensor monitors the air in the enclosure for smoke particles.
Material	Plastic
Surface finish	Front: Smooth Enclosure: Textured
Colour	RAL 7035
Supply includes	Sensor Mounting plate Mounting bracket Assembly parts
Connection to the CAN bus	Direct
Interfaces	2 x RJ45 CAN bus
Operating temperature range	0 °C...45 °C
Ambient humidity (non-condensing)	5...95 %
Packs of	1 pc(s).
Customs tariff number	85311095

Features

Product description

DK Smoke detector, linked via CAN bus interface

Approvals

Explanations

Declaration of conformity