### Rittal – The System.

Faster – better – everywhere.



## DK 7856.713 Mounting frame, 482.6 mm (19")

State: 31/07/2025 (Source: rittal.co gr-en)



# DK 7856.713 - Mounting frame, 482.6 mm (19") for TS, CS Basic and modular enclosures

For the installation of the front and rear 482.6 mm (19") levels, the welded 482.6 mm (19") mounting frame may be attached with complete depth variability.



#### **Features**

DK 7856.713
The welded 482.6 mm (19") mounting frame may be attached with complete depth variability and is used to structure the front and rear 482.6 mm (19") level. The mounting frame has the same system punchings as the TS 8 enclosure section at the sides and rear, and therefore supports the mounting of various TS 8 system accessories such as cable clamp rails, cable shunting rings etc.
Sheet steel
Zinc-plated
Assembly parts
Width: 482.6 mm
24 U
Up to 10,000 N static load, with even load distribution on two 482.6 mm (19") mounting frames, fully configured.
A combination of 482.6 mm (19") mounting frame plus fan mounting plate is not possible. For active ventilation, we recommend use with modular fan roof.

© Rittal 2025

#### **Features**

To fit	Enclosure type: TS 8
	CS basic enclosures
	CS modular enclosures
	Width: 600 mm
	Height: 1,200 mm
Packs of	1 pc(s).
Net weight	7.631
Gross weight	8.033
Customs tariff number	73269098
EAN	4028177402355
ETIM 9	EC002620
ECLASS 8.0	27189261

#### Tender text

FR(i)/TS 19" mounting frame, 24 U

Load capacity: Up to 1000 kg static load, with even load distribution on two 482.6 mm (19") mounting frames, with full installation.

A combination of 482.6 mm (19") mounting frames plus fan mounting plate is not possible. We recommend combined use with a modular fan roof for FR(i)/TS 8 for active ventilation. Captive nuts and assembly screws, TS 8 cable clamping rails, adjustable slide rails, component shelves, modular fan roof.

Material: Sheet steel, zinc-plated, passivated Dimensions (W x H): 600 mm x 1200 mm

© Rittal 2025 3